

LES Analysis of SI Combustion Process in a Hydrogen Unsteady Jet

***Hiroshi KAWANABE
Masahiro SHIOJI***

***School of Energy Science,
Kyoto University***

Hydrogen fueled Spark-ignition Engine Combustion Characteristics of H_2

- High Burning Velocity

 - Rapid Combustion (Knocking like Combustion)

- High Ignitability

 - Abnormal Burning (Backfire)


- to Achieve

 - Higher Output Power
and

 - Higher Thermal Efficiency


- Control the SI-Combustion

**Direct-injection Spark-ignition
System is Feasible for a Hydrogen Engine**



Visualization Image of DI-SI Combustion Process


Analysis of Spark-ignited Combustion Process of a High-speed Unsteady Hydrogen jet in CVV



- **Large Eddy Simulation**
 - **Mixing Process by Unsteady Fluid Motion**
- **Flame Propagation Model**
 - **G-equation Model**
to reduce calculation load

Contents


1. Comparison Calc. and Exp.
2. Mixture Formation Process
3. Flame Structure
4. Local Heat Release Rate




Calculation Condition

Fuel	Hydrogen
Injection Pressure p_j (MPa)	8
Ambient Pressure p_a (MPa)	0.5
Ambient Temperature T_a (K)	300
Nozzle Diameter d_0 (mm)	0.8
Ambient Gas	Air (O2: 21% N2: 79%)
Ignition Position (x,y,z) (mm)	(35,0,0)

SGS: Smagorinsky Model
($C_s=0.11$, $Sc_t=1.0$)



Pseudo-nozzle Concept



Pseudo-nozzle Concept (A.D.BIRCH □ 1983)

$$d_n = d_0 \sqrt{C_D \frac{p_j}{p_a} \left(\frac{2}{\gamma + 1} \right)^{\frac{\gamma + 1}{2(\gamma - 1)}}}$$

Ideal Gas □ Adiabatic Expansion

d_n : Pseudo-nozzle diam.

u_j, u_n : Sonic Speed

C_D : Flow Rate Coef.

γ : Specific Heat Ratio

Flame Propagation Model

$$\frac{\partial \bar{\rho} \tilde{G}}{\partial t} + \frac{\partial \bar{\rho} \tilde{G} \tilde{u}_j}{\partial x_j} = -\frac{\partial \mathcal{R}^{SGS}}{\partial x_j} + \bar{\rho}_u S_T |\nabla \tilde{G}|$$

ρ_u : Density of Unburned Gas

S_T : Turbulent Burning Velocity

\mathcal{R}^{SGS} : SGS-Scalar Flux of G



$$\frac{S_T}{S_L} = 1 + 1.25 \left(\frac{u'}{S_L} \right)^{0.7} \quad \begin{array}{l} u' : \text{SGS Fluctuation Intensity} \\ S_{ij} : \text{Strain Rate} \\ \Delta : \text{Filter Size} \end{array}$$

$$u' = 0.28 \Delta \sqrt{2 S_{ij} S_{ij}}$$

$$S_L = S_{L0} \left\{ 1 + \beta \log \left(\frac{p}{p_0} \right) \right\} \left(\frac{T_u}{T_{u0}} \right)^\alpha$$

$$\alpha = 1.54 + 0.025(\phi - 1)$$

$$\beta = 0.43 + 0.003(\phi - 1)$$




Burnt Gas Temperature (Diffusion Flame)

**Chemical Equilibrium
(Burned Gas)**


→ **Temperature**
Species Concentration
**Calculated based on the
Local Mixture Fraction**

Products(7 Species)


$H_2, O_2, N_2, H_2O, OH, O, H$



Combustion Process (compared with Exp.)






$t_i = 0.3\text{ms}$ (Ignited at Jet Tip Condition)






$t_i = 1.8\text{ms}$ (Ignited inside Jet Condition)

Flame Structure ($t_i = 1.8 \text{ ms}$)



Local Heat Release Ratio

Ignition Timing: $t_i = 1.8\text{ms}$ (Ignited inside Jet condition)



Heat Release Region
Front of Premixed Flame Area
↓
Diffusion Flame Area

Flame propagation process of a high-speed unsteady jet was successfully calculated by means of large eddy simulation with the G-equation flamelet and diffusion flame models

Change of combustion process is well predicted with different ignition timing.

Combustion progresses gradually with supplying fuel in the condition of a jet tip ignition. On the other hand, flame propagates quickly outward in the condition of ignition inside jet.

After the flame propagation, combustion progresses gradually at the stoichiometric region as a diffusion flame.