



INSTITUT PRISME


Institut Pluridisciplinaire de Recherche
Ingénierie des Systèmes, Mécanique, Énergétique

UNIVERSITE D'ORLEANS

The effect of hydrogen enrichment in strong dilution

Fabien HALTER

Toni Tahtouh, Christine Mounaïm-Rousselle



2

- ✓ Hydrogen has an elevated RON (130).
As a minor blending component, hydrogen seems to raise overall knock resistance.

- ✓ As hydrogen quantities are relatively small, the best solution could be an on-board production.
This can be achieved by a reformer.
- ✓ However, the gain in efficiency has to counter-balance the energy needed for hydrogen production.
Low load conditions are not favorable for the thermic of the reformer.


Hydrogen addition effect on the stability



- ✓ For low load conditions, EGR addition is limited by the engine stability.
- ✓ The first step is to show the benefic effect of hydrogen addition on the flame stability.
- ✓ Experiments were performed for low load conditions in a metal engine.

Engine specifications

Engine type	4 valves / cylinder
Displacement volume	499 cm ³
Bore	88 mm
Stroke	82 mm
Compression ratio	9,5
Connecting rod	137 mm

Experimental set-up



 Thermal mass flow meter/controller
 Coriolis flow controller

- ✓ 2 IMEP (2.8 and 4.0 bars)
- ✓ 4 EGR rates (0 – 10 – 15 – 20)
- ✓ 2 hydrogen blendings in the EGR (0 and 15% in vol.)


$$IMEP = \frac{\oint P dV}{V_c} [bar]$$

$$COV_{IMEP} = \frac{\sigma_{IMEP}}{IMEP} [\%]$$


σ_{IMEP} is the standard deviation of the indicated mean effective pressure

Ignition timing and intake pressure were optimised to find the maximum of the Indicated Mean Effective Pressure.


Experimental results - Stability



Experimental results – NO_x emissions



Experimental results – HC emissions



Conclusions on this first study


- ✓ EGR rate is limited by engine stability.
- ✓ Engine stability can be increased for low load conditions by hydrogen addition.
- ✓ This improvement is directly linked to the enhancement of the turbulent burning velocity.
- ✓
- ✓ This information will be measured experimentally.
- ✓ If we consider a flamelet approach, the turbulent burning velocity is linked to the turbulent flame surface and also to the laminar burning velocity.

- ✓ Propagation limits for different $\text{CH}_4\text{-H}_2\text{-N}_2$ -air mixtures
- ✓ Determination of laminar burning velocities for different N_2 dilution amounts (from 0 - 30%) and for different hydrogen additions (from 0 – 30%).

Experimental conditions:


$P_{\text{ini}}=0.1 \text{ MPa}$ – $T_{\text{ini}}=300 \text{ K}$ – $\text{ER}=1$

Experimental device




Laminar results extraction

- ✓ High speed recording of flame front temporel evolution




Laminar results extraction



$t = 1\text{ms}$

$t = 4\text{ms}$

$t = 9\text{ms}$



$t = 14\text{ms}$


$t = 19\text{ms}$

$t = 24\text{ms}$

Methane-air mixture with 20% H_2 addition and 20% N_2 dilution

Laminar results extraction


✓ The evolution of flame front radius




- ✓ The linear relation between laminar flame speed and stretch (Clavin) : $V_s = V_{s0} - L_b * K$
- ✓ Velocity evolution is obtained from radius evolution
- ✓ Flame stretch evaluation: $K = \frac{1}{A} * \frac{dA}{dt} = \frac{1}{2r_f} \frac{dr_f}{dt}$
- ✓ Linear extrapolation to a zero stretch rate for the calculation of the unstretched laminar flame speed
- ✓ Correction linked to the expansion factor
 (density ratio $\frac{\rho_b}{\rho_u}$)

✓ Determination of the propagation limits



✓ Using a visual criterion



✓ Laminar burning velocity



Laminar results - Conclusion

- ✓ Flammability limits are extended
 - ☑ 30% of Hydrogen addition  ~ +5% of N₂ dilution
- ✓ Laminar burning velocities are increased
 - ☑ 30% of Hydrogen addition  ~ +23% in u_{l0}

- ✓ Engine conditions:
 - ✓ A knock sensivity study when hydrogen is added.
A two zones modelisation with detailed chemistry.
 - ✓ Stabilisation study for high load conditions.
 - ✓ Turbulent burning velocities and flame front structure in an engine with optical accesses.

- ✓ Laminar conditions
 - ✓ Iso-octane
 - ✓ High pressure (20 bars) and temperature (450 K) conditions.



INSTITUT PRISME

Institut Pluridisciplinaire de Recherche
Ingénierie des Systèmes, Mécanique, Énergétique

UNIVERSITE D'ORLEANS

The effect of hydrogen enrichment in strong dilution

Fabien HALTER

Toni Tahtouh, Christine Mounaïm-Rousselle