

Back ground – (1)

Development of Gasoline HCCI Using Blow-Down Super Charging System

T. Kuboyama, Y. Moriyoshi (Chiba University, Japan)

K. Hatamura (HERO, Japan)

T. Yamada (CDAJ, Japan)

Y. Urata, J. Takanashi (Honda R&D, Japan)

- Advantages of gasoline HCCI engine
 - High thermal efficiency
 - Low exhaust gas emission
- Issues of gasoline HCCI engine
 - Extension of driving load
 - High load limitation
 - Increase in $dP/d\theta$ and NOx emission
 - Low load limitation
 - Incomplete combustion; Increase in instability of combustion and CO, HC emission
 - Control of auto-ignition timing


Back ground – (2)

- Previous attempts to solve HCCI problems

| | | |
|------------------------------|--|--|
| Extension of high load limit | Supercharge | Hyvonen, j., et al., SAE Paper No. 2003-01-3214, etc... |
| | Inter cylinder EGR (EGR + Supercharge) | Takanashi, J., et al., JSAE Annual congress 2006., Spring, JSAE 20066516 |
| | Thermal stratified | Nakano. H., et al., I.C. Engine symposium 19th, No. 06-251, A6-4, pp.387-392, etc... |
| | Direct inj. | Urata, Y., et al., SAE Paper No. 2004-01-1898 etc... |
| | Fuel stratified + Spark assist | Urushibara, T., et al. JSAE Annual congress 2004, Spring, JSAE 2004 5114, etc... |
| Extension of low load limit | NVO(Internal EGR) | Urata, Y., et al., SAE Paper No. 2004-01-1898 etc... |
| | DI during NVO period | Jacques, L., et al., SAE2000-01-1837, etc... |
| | Fuel stratified | Marriott, D.C., and Raitz, D. R, SAE Paper No. 2002-01-0418, etc... |

Back ground (3)

- HCCI operational range without supercharge




Objective

- To extend the high load operation limit of a gasoline HCCI engine, a new system which contains two new techniques is proposed. The first technique is "**Blow-Down Super Charging (BDSC) system**" and the other one is "**EGR guide**" for generating a large in-cylinder thermal stratification. In the present study, the performance of the proposed system is experimentally demonstrated.


Blow-Down Super Charging System (BDSC system)

- Exhaust valves re-open during early compression stroke to boost EGR by using the blow-down pressure wave of the other (360 deg. phase-shifted) cylinder.
- EGR boost is possible without external super charger.



EGR guide for creating in-cylinder thermal stratification

- Thermal stratification has a high potential to reduce steep pressure rise.
- To generate a large thermal stratification inside the cylinder, EGR guide is attached on the edge of the exhaust port and piston head.




Test engine & conditions

| | |
|-------------------|------------------------|
| Base engine | Honda K20A |
| Engine type | Inline 4 cylinder |
| Bore x Stroke | 86 mm x 86 mm |
| Displacement | 1998 cm ³ |
| Compression ratio | 12 (HCCI)/ 11.5 (Base) |
| Fuel injection | Port injection |
| Fuel | Gasoline (RON91) |
| Engine speed | 1500 rpm |
| Valve timing | Fixed cam |


Optimized valve lift & timing

➤ The valve timing used in the present study was optimized by using an optimization software (mode-FRONTIER) & 1-D numerical simulation code (GT-Power) for each target IMEP.



- High load operation
 - High intake valve lift and low EGR valve lift
- Low & mid. load operation
 - Low intake valve lift and high EGR valve lift
- Exhaust valve actuation;
 - Fixed (Independent of the load).

Measurement system




Definition of operational HCII

- Limit of maximum pressure rise rate
 - $dP/d\theta \max \leq 400 \text{ kPa/deg.}$
- Limit of combustion variation
 - $\text{COV. of IMEP} \leq 5 \%$
- Limit of NOx emission
 - $\text{ISNOx} \leq 0.1 \text{ g/kWh}$


Performance of BDSC-HCCI engine

- $P_{ex} = 130 \text{ kPa}$
- High load limit $\rightarrow dP/d\theta \max \text{ limit } (< 400 \text{ kPa/deg.})$
- Without EGR guide




Generation of In-cylinder thermal stratification using EGR guide


- 3-D simulation results




Effect of EGR guide on performance of BDSC-HCCI engine



Effect of EGR guide on performance of BDSC-HCCI engine



High load operation limit of BDSC-HCCI engine




Summary

- In order to extend high load operation limit of gasoline HCCI engine, a new system which consists of **"Blow-Down Super Charging (BDSC)"** and **"EGR guide"** walls for generating a large in-cylinder thermal stratification was proposed. The performance of the proposed system was experimentally demonstrated. Experimental results are as follows;

- BDSC system was experimentally evaluated as a technique to realize high load HCCI operation.
- Attaching the EGR guide on the edge of exhaust port and piston head, it is possible to decrease $dP/d\theta$ max at high load HCCI operation. This is probably due to a large thermal stratification inside the cylinder generated by EGR guide.

Summary

- Using the proposed system (BDSC system and EGR guide), HCCI operation at **IMEP of 650 kPa** (engine speed of 1500 rpm) which corresponds to the upper load of 10-15 Japanese test mode was achieved.



Acknowledgement

- The authors would like to mention that the present study was financially supported by NEDO. The authors would like to thank Kistler Japan, Co. Ltd., for their support for pressure measurement. And helpful discussion with Dr. Suzuki of Hatamura engine research office is also acknowledged.

Summary

- In order to extend high load operation limit of gasoline HCCI engine, a new system which consists of **"Blow-Down Super Charging (BDSC)"** and **"EGR guide"** walls for generating a large in-cylinder thermal stratification was proposed. The performance of the proposed system was experimentally demonstrated. Experimental results are as follows;
- BDSC system was experimentally evaluated as a technique to realize HCCI operation.
 - Attaching the EGR guide on the edge of exhaust port and piston head, it is possible to decrease $dP/d\theta$ max at high load HCCI operation. This is probably due to a large thermal stratification inside the cylinder generated by EGR guide.

Summary

3. Using the proposed system (BDSC system and EGR guide), HCCI operation at **IMEP of 650 kPa** (engine speed of 1500 rpm) which corresponds to the upper load of 10-15 Japanese test mode was achieved.

